

Product Features

Warranty: Two (2) Years. All Parts Serviceable and Stocked in the USA

Driver: Remote, 24V

<u>Circuit Type</u>: 24V, Constant Voltage, Class 2 Power Unit Only

Maximum Power Consumption: 5.0 Watts per foot

Beam Angle: 120°

Operating Temperature Range: -4°F to 122°F (-20°C to 50°C)

<u>Dimming</u>: Non-Dimming (Dimming option available)

Housing: Heat-Dissipating Aluminum, Adjustable Mounting Feet

Lens: Fire-Resistant Extruded Non-Yellowing Acrylic



4000K 5000K 373 428.9 1223.75 1406.792 ITL90957













Optional Power Cord SOOW: Heavy-duty Industrial Application, Service Cord, Oil-Resistant Inside Insulation and Outside Jacket, Sunlight Resistant, Length 72.0 IN. Optional Wall Mounting: Custom Pivot Bracket Direct in Length Increments of 2.0 IN, 6.0 IN, 12.0 IN, 18.0 IN, 24.0 IN



IES File Number:

Telephone (972) 721-1177 Innovative-Lighting.com 2324 Hinton Drive, Irving, TX 75061

Published 2020-OCT 26

Custom

Color Temperatures

Available